

Features

- $V_R=80V$
- $I_{F(AV)}=100mA$
- Power Dissipation of 250mW
- Fast switching speed
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260°C

SOD-323




Applications

For use in low voltage high frequency circuit signals.

Mechanical Data

- Case: SOD-323
Molding compound meets UL 94V-0 flammability rating, RoHS-compliant, halogen-free
- Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity: Cathode line denotes the cathode end







Maximum Ratings ($T_a=25^{\circ}C$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	VALUE
Non-Repetitive Peak Reverse Voltage	V_{RM}	V	90
Maximum repetitive peak reverse voltage	V_{RRM}	V	80
Maximum RMS Voltage	V_{RMS}	V	80
Reverse Breakdown voltage @ $I_R=0.1\mu A$	$V_{(BR)R}$	V	80
Maximum Average Forward Rectified Current	$I_{F(AV)}$	mA	100
Non-repetitive Peak Forward Current	I_{FM}	mA	225
Non-repetitive Peak Forward Surge Current @ $t=1s$	I_{FSM}	mA	500
Power Dissipation	P_d	mW	250
Storage temperature	T_{stg}	$^{\circ}C$	-55 ~ +150
Junction temperature	T_j	$^{\circ}C$	150
Typical thermal resistance	$R_{\theta J-A}$	$^{\circ}C / W$	625

Electrical Characteristics ($T_a=25^{\circ}C$ Unless otherwise specified)

PARAMETER	TEST CONDITIONS	SYMBOL	UNIT	Min	Max
Maximum instantaneous forward voltage	$I_F=100mA$	V_F	V	—	1.2
Reverse Leakage Current	$V_R=80V$	I_R	μA	—	0.1
Total capacitance	$V_R=0.5V, f=1MHz$	C_T	pF	—	3.0
Maxinum reverse recovery time	$I_F=I_R=10mA, V_R=6V$ $I_{rr}=0.1 \times I_R, R_L=100\Omega$	T_{rr}	ns	—	4.0


Ratings And Characteristics Curves (Ta=25°C Unless otherwise specified)




Ordering Information

PACKAGE	PACKAGE CODE	UNIT WEIGHT(g)	REEL(pcs)	BOX(pcs)	CARTON(pcs)	DELIVERY MODE
SOD-323	R1	0.0048	3000	30000	120000	7"

Package Outline Dimensions (SOD-323)

	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	1.60	1.80	0.063	0.071
B	0.25	0.40	0.010	0.016
C	2.30	2.80	0.091	0.110
D	0.80	1.10	0.031	0.043
D ₁	0.80	0.90	0.031	0.035
E	1.20	1.40	0.047	0.055
F	0.08	0.18	0.003	0.007
L	0.475REF		0.019REF	
L ₁	0.25	0.40	0.010	0.016
H	-	0.14	-	0.006

Suggested Pad Layout

	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
J	0.80	-	0.031	-
K	-	1.40	-	0.055
M	0.80	-	0.031	-