

Features

- Power dissipation of 200mW
- High stability and high reliability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C




Function Diagram

Collector-Base Voltage
VCBO 60V
Collector Current
0.1 Ampere

Mechanical Data

- Case: SOT-23
- Molding compound meets UL 94V-0 flammability rating, RoHS-compliant, halogen-free
- Terminals: Solder plated, solderable per MIL-STD-750, Method 2026

XX = Device Code
L4 = 2SC1623-L4
L5 = 2SC1623-L5
L6 = 2SC1623-L6
L7 = 2SC1623-L7



Package Marking and Ordering Information

Product ID	Pack	Marking	Qty(PCS)
2SC1623	SOT-23	XX	3000

Absolute Maximum Ratings (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	UNIT	VALUE
Collector-Base Voltage	V _{CBO}	V	60
Collector-Emitter Voltage	V _{CEO}		50
Emitter-Base Voltage	V _{EBO}		5.0
Collector Current	I _C	A	0.1
Collector Power Dissipation	P _C	mW	200
Storage temperature	T _{stg}	°C	-55 ~ +150
Junction temperature	T _j	°C	-55 ~ +150
Typical Thermal Resistance	R _{θJA}	°C /W	417

Electrical Characteristics (T_a=25°C Unless otherwise noted)

PARAMETER	SYMBOL	UNIT	Condition	Min	Max
Collector-Base Breakdown Voltage	V _{(BR)CBO}	V	I _C =100μA, I _E =0	60	—
Collector-Emitter Breakdown Voltage	V _{(BR)CEO}		I _C =1.0mA, I _B =0	50	—
Emitter-Base Breakdown Voltage	V _{(BR)EBO}		I _E =100μA, I _C =0	5.0	—
Collector-Base cut-off current	I _{CBO}	nA	V _{CB} = 60V, I _E =0	—	100
Emitter-Base cut-off current	I _{EBO}		V _{EB} = 5.0V, I _C =0	—	100
DC Current Gain	h _{FE}	—	I _C =1.0mA, V _{CE} = 6.0V	90	600
Collector-Emitter Saturation Voltage	V _{CE(sat)}	V	I _C = 100mA, I _B = 10mA	—	0.3
Base-Emitter Saturation Voltage	V _{BE(sat)}	V	I _C = 100mA, I _B = 10mA	—	1.0

Classification Of h_{FE}

RANK	L4	L5	L6	L7
Range	90-180	135-270	200-400	300-600





Small-signal Characteristics

ITEM	SYMBOL	Condition	UNIT	Min	Typ	Max
Transition frequency	f_T	$I_C=10\text{mA}$, $V_{CE}=6.0\text{V}$	MHz	—	250	—



Ordering Information

PACKAGE	PACKAGE CODE	UNIT WEIGHT(g)	REEL(pcs)	BOX(pcs)	CARTON(pcs)	DELIVERY MODE
SOT-23	R1	0.008	3000	30000	120000	7"


Ratings And Characteristics Curves ($T_a=25^\circ\text{C}$ Unless otherwise specified)



Ratings And Characteristics Curves ($T_a=25^\circ\text{C}$ Unless otherwise specified)



Package Outline Dimensions (SOT-23)



Suggested Pad Layout

